

TIRE FITMENT CHART

This sizing chart is designed as a guideline to provide the maximum/minimum tire size and rim width for a given lift application. Body and or fender modifications may be required to properly install the maximum tire diameter and maximum wheel width listed. In most cases modifications consist of minimal trimming of plastic bumper valances and or plastic fender liners. Use of maximum width or minimum backspace is more likely to result in tire to fender contact and require modification. Before installation and operation of any tire and wheel combination, be certain there is no interference with brake, suspension and steering components and body/fender panels. Excessive tire diameter, wheel width and or improper rim backspacing may cause premature wear and/or failure of brake components, suspension and steering components as well as possible body damage. The rim dimension information for this guide is from an individual wheel manufacturer. Wheel manufacturers and tire manufacturers design specifications vary and Pro Comp Suspension is not responsible for damages resulting from the incorrect choice of wheel and tire combination.

YEAR	DESCRIPTION	MAX TIRE (INCHES)	RIM DIAMETER RANGE (INCHES)	RIM WIDTH RANGE (INCHES)	BACKSPACE MIN (INCHES)	BACKSPACE MAX (INCHES)
GM vehicles						
2007	6" GMT900 Platform Pickup / SUV	35x12.50	17-20	8-9	4.5	5
00-06	6" K1500HD / 2500 HD 2WD / 4WD	35x12.50	16-20	8-9.5	4	5
00-06	6" 2500 Avalanche / Suburban 4WD	35x12.50	16-20	8-9.5	4	5
99-06	6" K1500 Silverado/Tahoe/Yukon 4WD	35x12.50	16-20	8-9.5	4	5
99-06	5" K1500 Silverado 4WD (knuckle kit)	33x12.50	16-20	8-9	4	4.65
99-06	3" 2WD Silverado	31x10.50	16-20	8-9	4	4.5
00-06	6" Avalanche 4WD with body cladding	35x12.50	16-20	8-9.5	4.5	5
00-06	6" Avalanche 4WD without body cladding	35x12.50	16-20	8-9.5	4	5
99-06	6" 2WD Silverado	35x12.50	16-20	8-9.5	4	4.65
00-06	6" 2WD Avalanche / Tahoe / Yukon	35x12.50	16-20	8-9	4	4.65
88-99	3" 2WD C1500 Chevy	32x11.50	15-16	8	3.25	3.75
88-98	4" IFS Chevy 6 Lug	33x12.50	15-20	8-9	3.25	5
88-98	6" IFS Chevy 6 Lug	35x12.50	15-20	8-9	3.25	5
88-98	6" IFS Chevy 8 Lug	35x12.50	15-20	8-9	4	5
73-87	2.5 Chevy 6 Lug	33x12.50	15-20	8-10	3.25	4.5
73-87	4" Chevy 6 Lug	33x12.50	15-20	8-10	3.25	4.5
73-87	6" Chevy 6 Lug	35x12.50	15-20	8-10	3.25	4.5
73-87	2.5 Chevy 8 Lug	33x12.50	16-20	8-10	3.25	4.5
73-87	4" Chevy 8 Lug	33x12.50	16-20	8-10	3.25	4.5
73-87	6" Chevy 8 Lug	35x12.50	16-20	8-10	3.25	4.5

GM notes
2005 and newer GM 1500 6 lug models require 17" or larger diameter rims due to changes of factory brake components. A maximum backspace of 4.5" is recommended when using Pro Comps multiple shock hoop kits to provide adequate clearance between the rim and lower shock mounting hardware and between the tires and shock absorbers.

Dodge vehicles

03-07	5" Dodge 2500 Heavy Duty 4WD	37x12.50	17-20	8-10	4	5
03-07	3" Dodge 2500 Heavy Duty 4WD	35x12.50	17-20	8-10	4	5
03-07	2" Dodge 2500 Heavy Duty 4WD	33x12.50	17-20	8-10	4	5
94-02	2" Dodge 2500 4WD	33x12.50	16-20	8-10	3.25	4.5
06-07	5" Dodge 1500 4WD	35x12.50	18-20	8-9	4	4.5
02-05	4.5" Dodge 1500 4WD	35x12.50	17-20	8-9	4	4.5
94-01	3" Dodge 1500 4WD	33x12.50	15-20	8-10	3.25	4.5
02-05	6" Dodge Ram 1500 2WD	35x12.50	17-20	8-9	4	4.5
94-99	3" Dodge Ram 1500 2WD	32x11.50	15-16	8	3.25	3.5

Ford vehicles

05-07	2" Ford Super Duty 4WD	33x12.50	16-20	8-10	4	5.75
05-07	6" Ford Super Duty 4WD	35x12.50	16-20	8-10	4	5.75
05-07	8" Ford Super Duty 4WD	37x13.50	16-20	8-10	4	5.75
99-04	2" Ford Super Duty / Excursion 4WD	33x12.50	16-20	8-10	4	5
99-04	4" Ford Super Duty / Excursion 4WD	35x12.50	16-20	8-10	4	5
00-04	6.5" Ford Super Duty 4WD	37x13.50	16-20	8-10	4	5
00-04	8.5" Ford Super Duty 4WD	37x13.50	16-20	8-10	4	5
04-07	6" F-150 4WD / 2WD	35x12.50	17-20	8-9.5	4	5
04-07	2.5" F-150 4WD / 2WD	33x12.50	17-20	8-9.5	4	5
97-03	4" Ford F150 4WD	35x12.50	16-20	8-9.5	3.5	4.5
80-96	4" Ford F150 4WD	33x12.50	15-20	8	3.25	4
80-96	6" Ford F150 4WD	35x12.50	15-20	8	3.25	4

continued

TIRE FITMENT CHART

YEAR	DESCRIPTION	MAX TIRE (INCHES)	RIM DIAMETER RANGE (INCHES)	RIM WIDTH RANGE (INCHES)	BACKSPACE MIN (INCHES)	BACKSPACE MAX (INCHES)
Ford vehicles continued						
			see notes			
99-04	6" 2WD Ford Super Duty	35x12.50	16-20	8-9.5	3.5	4.5
00-04	6" 2WD Ford Excursion	35x12.50	16-20	8-9.5	3.5	4.5
97-03	3" 2WD Ford F150	32x11.50	16-18	8	3.5	4
97-03	6" 2WD Ford F150	35x12.50	16-20	8-9.5	3.5	4.5
80-96	2" Ford F150	31x10.50	15-20	8	3.25	4
80-96	4" 2WD Ford F150	32x11.50	15-20	8	3.25	4
80-96	6" 2WD Ford F150	33x12.50	15-20	8	3.25	4
98-05	3" 2WD Ranger	31x10.50	15-17	8	3.25	4
93-97	5" 2WD Ford Ranger	31x10.50	15-17	8	3.25	4
86-92	5" 2WD Ford Ranger	30x9.50	15	7	3.25	4
95-00	3" 2WD Explorer	31x10.50	15-17	8	3.25	4

Jeep vehicles

97-06	2" Jeep TJ / LJ Wrangler / Rubicon / Unltd	32x11.50	15-17	8-9	3.25	4.5
97-06	4" Jeep TJ / LJ Wrangler / Rubicon / Unltd	33x12.50	15-17	8-10	3.25	4.5
87-96	2.5" Jeep YJ Wrangler	31x10.50	15-17	8	3.25	4.5
87-96	4" Jeep YJ Wrangler	33x12.50	15-17	8-10	3.25	4.5
87-96	5" Jeep YJ Coil Spring Conversion	33x12.50	15-17	8-9	3.25	4.5
76-86	2.5" Jeep CJ	32x11.50	15-17	8-10	3.25	4
76-86	4" Jeep CJ	33x12.50	15-17	8-10	3.25	4
84-01	3" Jeep XJ Cherokee	30x9.50	15-17	7-8	3.25	4.5
92-98	3" Jeep ZJ Grand Cherokee	30x9.50	15-17	7-8	3.25	4.5
99-04	2" Jeep WJ Grand Cherokee	30x9.50	16-20	8-9	4	5.5
05-06	2" Jeep WK Grand Cherokee	30x9.50	17-20	8-9	4	5.5

Nissan vehicles


04-06	6" Nissan Titan 4WD / 2WD	35x12.50	17-20	8-9.5	4.25	5
04-06	6" Nissan Armada 4WD / 2WD	35x12.50	17-20	8-9.5	4.25	5
04-06	2.5" Nissan Titan 4WD / 2WD	33x12.50	17-20	8-9.5	4.25	5
04-06	2" Nissan Xterra	31x10.50	16-18	8-9	4.25	5

Toyota vehicles

2007	5" Toyota FJ Cruiser	35x12.50	18-20	8-9	4	4.65
05-07	6" Toyota Tacoma 4WD / Prerunner 2WD	35x12.50	17-20	8-9	4	4.65
05-07	6" Toyota Tacoma 4WD / Prerunner 2WD	33x12.50	17-20	8-9	4	4.65
05-07	2.5" Toyota Tacoma 4WD / Prerunner 2WD	32x11.50	16-20	8-9	4	5
96-04	4" Toyota Tacoma 4WD / Prerunner 2WD	32x11.50	15-17	8	3.25	4.5
93-98	4" Toyota T-100/ IFS	33x12.50	15-17	8	3.25	4
86-95	4" Toyota p/u	33x12.50	15-17	8	3.25	4
79-84	3" Toyota p/u	32x11.50	15-17	8	3.25	4
79-84	4" Toyota p/u	33x12.50	15-17	8	3.25	4
64-80	2.5" Toyota Land Cruiser	33x12.50	15-17	8-10	3.25	4

Toyota notes:
Factory 17" rims with factory tires can be used with the Pro Comp 05-06 Tacoma suspension systems.
Factory 16" or 17" and aftermarket 16" or 17" rims cannot be used with 2007 FJ Cruiser suspension systems.

#1 Tire Terms:



#2 Backspace: is the distance from the hub-mounting surface to the back edge of the rim.