

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Offset
Chevrolet / GM / GMC							
07-12	K1500, Avalanche, Tahoe, SUV, Etc.(Coil-Over Assembly) ^{1,2,3}	2"	265	75	17"	8"	OEM
		3"	285	75	17"	8"	4.5"
		6"	315	75	17"	8"	4.5"
00-06	Cadillac Escalade, ESV, EXT ^{1,3}	3"	285	75	16"/17"	8"	4.5"
04-12	Colorado/Canyon 4WD ²	4"	285	70	17"	8"	4.75"
00-06	Tahoe/Yukon/Sub-urban 4WD ²	3"	285	75	16"	8"	4.5"
		6"	285	75	16"	8"	4.5"
00-06	Denali/Yukon XL 4WD ²	3"	285	75	16"	8"	4.5"
02-06	Avalanche 4WD ²	3"	285	75	16"	8"	4.5"
		6"	315	75	16"	8"	4"
02-08	Hummer H2 4WD	5.5"	38"	12.5"	17"	9"	4.5"
11-12	GM 2500HD 4WD	7"	37"	12.5"	17"	8"	5-5.26"
		7"	37"	12.5"	18"	8-9"	5-5.5"
		7"	37"	12.5"	20"	8.5-10"	5-6"
01-10	GM 2500HD 4WD ^{2,3}	3"	285	75	16	8"	4.5"
		6"	315	75	16"	8"	4"
01-08	1500HD, 2500	6"	315	75	16"	8"	4"
99-06	K1500 IFS 4WD ^{2,3}	3"	285	75	16"	8"	4.5"
		6"	315	75	16"	8"	4.5"
88-98	Full-Size IFS 4WD ²	2.5"	285	75	15"	8-9"	4.5"
		6"	35"	12.5"	15"-16"	8-9"	4.5"
88-91	Full-Size Blazer, Jimmy, Suburban 4WD	2.5"	33"	12.5"	15"-16"	8-9"	3.5"- 4"
		4"	35"	12.5"	15"-16"	8-9"	3.5"- 4"
		6"	37"	12.5"	15"-16"	8-9"	3.5"- 4"
		8"	39"	12.5"	15"-16"	10"	3.5"- 4"
73-87	Full-Size 4WD	2.5"	33"	12.5"	15"-16"	10"	3.5"- 4"
		4"	35"	12.5"	15"-16"	10"	3.5"- 4"
		6"	37"	12.5"	15"-16"	10"	3.5"- 4"
		8"	39"	12.5"	15"-16"	10"	3.5"- 4"
67-72	Full-Size 4WD	2.5"	34"	12.5"	15"-16"	10"	3.5"- 4"
		4"	36"	12.5"	15"-16"	10"	3.5"- 4"
		6"	38"	12.5"	15"-16"	10"	3.5"- 4"
		8"	40"	12.5"	15"-16"	10"	3.5"- 4"
DODGE							
09-12	Ram Pickup 1500 4WD ³	4"	35"	12.5"	18"-20"	8-10"	5"
		6"	37"	12.5"	18"-20"	8-10"	5"
06-07	Ram Pickup 1500 4WD ³	2"	33"	12.5"	17"	9"	OEM
02-05	Ram Pickup 1500 4WD ²	6"	37"	12.5"	17"	9"	5"
03-12	Ram 2500, 3500 Pickup 4WD Mega Cab ²	3"	34"	12.5"	15"-16"	10"	4.625"
		5"	37"	12.5"	15"-16"	10"	4.625"
94-01	Ram Pickup 4WD	2"-3"	33"	12.5"	15"-16"	10"	4.625"
		4"-5"	35"	12.5"	15"-16"	10"	4.625"
		7"	38"	12.5"	15"-16"	10"	4.625"

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Offset
61-93	Full-Size 1500, 2500 4WD	2"	33"	12.5"	15"-16"	10"	4"
		4"	35"	12.5"	15"-16"	10"	4"
		6"	37"	12.5"	15"-16"	10"	4"
		8"	39"	12.5"	15"-16"	10"	4"
FORD F-150, Bronco, Expedition							
09-12	F-150 4WD ²	2"	33"	12.5	17"	8"	5"
		6"	35"	12.5	20"	9"	5"
04-08	F-150 4WD, 2WD ^{2,3}	2"-3"	285	75	16"	8"	4.5"
04-08	F-150 4WD, 2WD ²	6"	315	75	16"	8"	4.5"
97-03	F-150 4WD	6"	35"	12.5"	16"	8"	4.5"
92-96	F-150, Bronco 4WD, 2WD	2"	32"	12.5"	15"	10"	4"
		4"	33"	12.5"	15"	10"	4"
		6"	35"	12.5"	15"	10"	4"
		8"	37"	12.5"	15"	10"	4"
87-91	F-150, Bronco 4WD, 2WD	2"	34"	12.5"	15"	10"	4"
		4"	36"	12.5"	15"	10"	4"
		6"	38"	12.5"	15"	10"	4"
		8"	39"	12.5"	15"	10"	4"
80-86	F-150, Bronco 4WD, 2WD	2"	33"	12.5"	15"	10"	4"
		4"	35"	12.5"	15"	10"	4"
		6"	37"	12.5"	15"	10"	4"
		8"	38.5"	12.5"	15"	10"	4"
69-79	F-150, 78-79 Bron-co 4WD	2"	33"	12.5"	15"	10"	4"
		4"	35"	12.5"	15"	10"	4"
		6"	37"	12.5"	15"	10"	4"
		9"	40"	12.5"	15"	10"	4"
66-77	Bronco 4WD with Cut-Outs	3"	33"	12.5"	15"	10"	4"
		5"	35"	12.5"	15"	10"	4"
		7"	37"	12.5"	15"	10"	4"
03-08	Expedition 4WD	2"	32"	11.5"	16"	8"	3.625"
FORD 66-09 F-250, F-350							
05-12	F-250, F-350 4WD Super Duty ²	1"	32"	12.5"	16.5"	9"	5"
		2"	33"	12.5"	16.5"	9"	5"
		4"	35"	12.5"	16.5"	9"	5"
		6"	36"	12.5"	16.5"	9"	5"
		8.5"	38"	12.5"	16.5"	9"	5"
99-04	F-250, F-350 4WD Super Duty	2"	33"	12.5"	16.5"	9.75"	4.625"
		4"	35"	12.5"	16.5"	9.75"	4.625"
		6"	36"	12.5"	16.5"	9.75"	4.625"
		8"	38"	12.5"	16.5"	9.75"	4.625"
92-98	F-350 4WD Mono Beam	2"	34"	12.5"	16.5"	9.75"	4.625"
		4"	36"	12.5"	16.5"	9.75"	4.625"
		6"	38"	12.5"	16.5"	9.75"	4.625"
86-91	F-350 4WD Mono Beam	2"	36"	12.5"	16.5"	9.75"	4.625"
		4"	38"	12.5"	16.5"	9.75"	4.625"
		6"	40"	12.5"	16.5"	9.75"	4.625"
92-98	F-250 4WD Twin I Beam	2"	33"	12.5"	16.5"	9.75"	4.625"
		4"	35"	12.5"	16.5"	9.75"	4.625"
		6"	37"	12.5"	16.5"	9.75"	4.625"
80-91	F-250, F-350 4WD Twin I Beam	2"	33"	12.5"	16.5"	9.75"	4.625"
		4"	35"	12.5"	16.5"	9.75"	4.625"
		6"	37"	12.5"	16.5"	9.75"	4.625"

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Offset
92-96	F-250, F-350 2WD	2"	32"	12.5"	16"	8"	3.75"
		4"	34"	12.5"	16"	8"	3.75"
		6"	36"	12.5"	16"	8"	3.75"
78-79	F-250 Low Boy 4WD	2"	35"	12.5"	16.5"	9.75"	3.75"
		4"	37"	12.5"	16.5"	9.75"	3.75"
		6"	40"	12.5"	16.5"	9.75"	3.75"
66-77	F-250 High Boy 4WD	2"	38"	12.5"	16.5"	9.75"	3.75"
		4"	40"	12.5"	16.5"	9.75"	3.75"
FORD Ranger, Bronco II, Explorer, Navajo							
93-97	Ranger 4WD	2"	32"	12.5"	15"	8"	4"
		4"	33"	12.5"	15"	8"	4"
		6"	34"	12.5"	15"	8"	4"
		8"	36"	12.5"	15"	8"	4"
90-94	Explorer, Navajo 4WD	2"	31"	12.5"	15"	8"	4"
83-92	Ranger, Bronco II 4WD	2"	28"	12.5"	15"	8"	4"
		4"	30"	12.5"	15"	8"	4"
		6"	32"	12.5"	15"	8"	4"
HONDA							
06-12	Ridgeline 4WD ²	2"	275	60	17"	8"	5"
72-82	Scout II 4WD	2"	31"	12.5"	15"	8"	3.75"
72-82	Scout II 4WD	4"	33"	12.5"	15"	8"	3.75"
ISUZU							
05-06	Isuzu i-Series	4"	285	75	17"	8"	4.75"
JEEP							
07-12	Wrangler JK 2-Door & 4-Door ^{1,2}	2"	33"	12.5"	16"	8	4.5
		2.5-3.5"	305	75	16"	8"	4.5
		4-5"	35"	12.5"	16"	8"	4.5
		6-7"	37"	12.5"	16"	8"	4.5
04-06	Wrangler Unlimited, Rubicon	2"	32"	11.5"	15"	8"	3.75"
		4"	34"	12.5"	15"	8"	3.75"
		6"	35"	12.5"	15"	10"	3.75"
		8"	37"	12.5"	15"	10"	3.75"
97-03	Wrangler TJ	2"	32"	11.5"	15"	8"	3.75"
		4"	34"	12.5"	15"	8"	3.75"
		6"	35"	12.5"	15"	10"	3.75"
		8"	37"	12.5"	15"	10"	3.75"
		10"	38"	12.5"	15"	10"	3.75"
87-96	Wrangler YJ	2"	31"	10.5"	15"	8"	3.75"
		4"	33"	12.5"	15"	8"	3.75"
		6"	35"	12.5"	15"	8"	3.75"
55-86	CJ and Scrambler	2"	31"	12.5"	15"	8"	3.75"
		4"	33"	12.5"	15"	10"	3.75"
05-12	Grand Cherokee WK 4WD, 2WD ²	2"	245	70	17"	8"	OEM
99-04	Grand Cherokee WJ 4WD	2"	31"	10.5"	16"	8"	3.75"
93-98	Grand Cherokee ZJ 4WD, 2WD	3"	31"	10.5"	15"	8"	3.75"
08-12	Liberty 4WD, 2WD	2.5"	265	50	20"	10"	OEM
02-07	Liberty 4WD, 2WD ¹	2.5"	245	75	16"	9"	OEM

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Offset
84-01	Cherokee XJ 4WD, 2WD	2"	30"	9.5"	15"	7"	3.75"
		3"	31"	10.5"	15"	8"	3.75"
		6"	33"	12.5"	15"	8"	3.75"
		8"	35"	12.5"	15"	8"	3.75"
06-12	Jeep Commander XK ²	2"	245	70	17"	8"	OEM
86-92	Comanche 4WD, 2WD	3"	31"	10.5"	15"	8"	3.75"
74-91	J10, J20, Cherokee, Wagoneer	4"	35"	12.5"	15"	10"	3.75"
NISSAN							
04-11	Titan 4WD ²	2.5"	285	75	18"	7"	5
04-11	Armada 4WD ²	2.5"	285	75	18"	7"	5
TOYOTA							
07-12	FJ Cruiser ²	2"	265	75	17"	8"	OEM
		3"	285	75	17"	8"	4.5
01-04	Sequoia 4WD	2.5"	32"	11.5"	16"	8"	3.5"
00-06	Tundra 4WD	2"	32"	11.5"	16"	8"	3.5"
00-06	Tundra 4WD	3"	32"	11.5"	16"	8"	3.5"
07-12	Tundra 4WD	2"	32"	11.5"	16"	8"	3.5"
		3"	32"	11.5"	16"	8"	3.5"
		6"	35"	12.5"	17"	8"	4.5"
05-12	Tacoma 4WD, Pre-Runner 2WD ²	2"	31"	11.5	16	8"	4.5"
		2.5"-3"	285	75	16"	8"	4.5"
96-04	Tacoma 4WD, Pre-Runner 2WD	2.5"-3"	31"	10.5"	15"	8"	3.5"
86-95	IFS Pickup 4WD	4"	33"	12.5"	15"	8"	3.75"
96-01	4Runner 4WD	2.5"	31"	11.5"	15"	8"	3.5"
84-85	Pickup, 4Runner 4WD	3"	33"	12.5"	15"	8"	3.75"
		5"	35"	12.5"	15"	8"	3.75"
		7"	37"	12.5"	15"	8"	3.75"
79-83	Pickup, 4Runner 4WD	3"	35"	12.5"	15"	8"	3.75"
		5"	37"	12.5"	15"	8"	3.75"
		7"	39"	12.5"	15"	8"	3.75"
91-97	FJ80 LandCruiser 4WD	2.5"	33"	12.5"	15"	8"	3.75"
64-80	LandCruiser 4WD	2"	32"	12.5"	15"	8"	3.75"
		4"	35"	12.5"	15"	8"	3.75"