



## Personal Protective Equipment

All personal protective equipment (PPE) must be inspected before use for damage. If any damage is found, (holes, tears, cracks, missing pieces, alterations etc.) Replace damaged PPE before continuing work.

All shared PPE must be cleaned before and after every use. (Wash with soap and water or use alcohol-based lens wipes).

### Safety Glasses

- Must always be worn in the Service Area. This includes the tire storage area.
  - Prescription safety glasses are available at no charge to all employees.
  - Must meet ANSI Z87.1 standard.

### Safety Goggles (Shared)

- Must be worn when using a hammer to remove stuck/damaged lugs or wheel locks.
  - Must meet ANSI Z87.1 standard.

### Face Shield (Shared)

- Must be worn when performing a flat repair.
  - Must meet ANSI Z87.1 standard.

### Earmuffs (Shared)

- Must be worn when using or assisting with the HTS tool or CR-Kit inflation assist tool.

### Gloves

- Minimum of ANSI Cut level A3.
- Must be worn when servicing vehicles, this includes air checks.
- Gloves can be removed in the following situations, only if absolutely necessary, but must be put back on immediately following completion of the task.
  - Threading on difficult lug nuts by hand. (Gloves must be worn when using the impact gun).
  - Rebuilding TPMS.
  - Removing backing from tape weights.
  - Removing backing from patch during a flat repair.
  - Using the dunk tank.
- Fingerless gloves, latex or nitrile type medical gloves worn alone or gloves that do not cover the palm or top of hand do not meet the requirement.



CRITICAL TO  
SAFETY