



## What We Can Service, Put Into Service, or Inflate



**CRITICAL TO SAFETY**

**Definitions:**

**Service** – To mount on a wheel, balance, or repair

**Put Into Service** – To install on a vehicle's axle for the first time (vehicle did not arrive with assemblies installed)

**Inflate** – To connect to an inflation device and adjust the air pressure

CONDITION	SERVICE	PUT INTO SERVICE	INFLATE	SELL
10 Years Old or Older Tires (See Manager/Senior Assistant)	🚫	🚫	✓	N/A
14.5, 15.5, 16.5, 17.5, or 19.5 (19.5 for approved stores only)	✓	✓	✓	✓
2/32nds or Less	🚫	🚫	✓	🚫
22.5 or 24.5	🚫	🚫	🚫	✓
Beadlock Wheels - ATV/UTV (for approved stores only)	✓	✓	✓	✓
Beadlock Wheels - Non-ATV/UTV	<a href="#">See Beadlocks – What We Service/Sell Best Practice</a>			
Bolt Together Wheels	🚫	🚫	🚫	N/A
Incorrect Wheel Width for Tire	✓ <small>(Balance and repair only)</small>	🚫	✓	🚫
Load Capacity Exceeded (On vehicle)	🚫	🚫	✓	N/A
Non-USTMA Repair	🚫	🚫	✓	N/A
Passenger or Light Truck Tires with Less Than 15 PSI (without an off-the-wheel inspection)	🚫	🚫	🚫	N/A
Plastic Wheels	🚫	🚫	🚫	N/A
Portable Air Tanks	🚫	🚫	🚫	N/A
Split Rims	🚫	🚫	🚫	N/A
Steel Sidewall Tires with 15 PSI or Less Than the Recommended Inflation Pressure (without an off-the-wheel inspection)	🚫	🚫	🚫	N/A

### ***The Whys***

- While not ideal, tires with the four inflatable conditions perform better with proper inflation.
- We are not equipped to prevent our people from being seriously injured when a 19.5 or 22.5 fails.
  - Steel sidewall damage on 19.5 and 22.5 tires are harder to detect. Zipper failures can occur at any time.
  - Due to the high pressure and construction of these tire sizes, a failure is likely to cause serious injury.
- We cannot inflate portable air tanks because they are not regulated or tested for safety.
- Plastic wheels are more susceptible to catastrophic failure.
- Plastic wheels can explode as the tires are filled with air, sending plastic shrapnel flying.
- When bolt together/split rims fail, parts of the wheel can be dangerously propelled from the assembly.
- Tires driven on with under 15 PSI are more likely to have unseen internal damage.