



## UNIVERSAL BARRIER-FREE VERSACOOLER® Energy and Water Conservation Technology

### PG8ACSL, PGACSL

#### Suggested Specification

Model PG8ACSL shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Model PGACSL is a non-refrigerated drinking fountain and delivers ambient water. Models PG8ACSL and PGACSL shall include front and side push pads to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Water Saver Bubbler shall reduce waste water by 50%. Bubbler shall have a flexible guard and operate between 20 and 120 PSI. Cabinet finish shall be Sandstone powder coated paint on galvanized steel or brushed stainless steel. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA. Shall comply with ANSI/NSF 61 Annex G.

#### Model

PG8ACSL delivers 8.0 gallons of chilled drinking water per hour. PGACSL is a non-refrigerated fountain.

#### Standard Features

- > Universal design includes a universal side access panel and universal drain pipe that allows the unit to be installed left high, right low or right high, left low
- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are Lead-Free in Materials & Construction
- > Stainless Steel top
- > Flexible, one-piece Water Saver Bubbler
- > Heavy Duty galvanized steel frame
- > High Efficiency cooling tank and coil
- > Refrigerant R-134a
- > Four push pad activation
- > External stream height adjustment

#### Finishes

- > Standard cabinet finish: Sandstone powder coated paint galvanized steel
- > Optional finishes (at additional cost): Stainless Steel, Regency Bronze, and optional powder coated finishes

#### Installation

- > Prior to roughing, consult with local, state and federal codes for proper mounting height
- > Shipped with complete instructions and wall mounting bracket
- > Universal side access panel and universal drain pipe for right high or left high installation included
- > Removable side and front panels provide easy access for installation



Energy & Water Conservation Model

Can be installed  
left high and right  
low...  
or

right high and  
left low.

#### Options

- Glass Fillers (factory installed)
- Push Handle (029603-004)
- Push Down (029603-006)
- Push Back (029603-005)
- One Piece Chrome Plated Brass Bubbler (036700-001)
- Apron for Upper Unit

**Powder Coated Finish Warranty** (Continental limits of the United States and Canada): Three years on the powder coat finish provided that the water cooler has not been subjected to abuse, misuse or alteration.

**Limited 5-Year Warranty** (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty:** One year on the sealed refrigeration system and most common parts. Detailed warranty certificate enclosed with each drinking fountain; sample available upon request

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.

ADA Compliant when installed in alcove or with right wing wall, or with accessory apron, or with a right wing wall for a right high unit or left wing wall for a left high unit.

Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Product Certified to NSF/ANSI Standard 61, Annex G and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953) weighted average lead content <=0.25%.



Oasis International Product  
Certified by NSF to  
ANSI/NSF Standard 61, G

Model	50° F Drinking Water 90° F Ambient Air Temp*				Hot 'N Cold™ Model**	115 Volts, 60 HZ				Glass Filler Acc. Option	Cabinet Color Finish	Net Wt Approx
	Rated Ca- pacity GPH	Base Rate GPH	Pre-Cooler	Compr. HP		Full Load Amps	Rated Watts					
PG8ACSL**	8.0	8.0	No	No	1/4	4.4	500	Yes	Yes	84 Lbs.		
PGACSL				Fountain Only				Yes	Yes	50 Lbs.		

\*Industry Standard Rating Condition 80°F inlet water temperature.

\*\*Special export models available, operable on 220- 240 volts, 50/60 Hz. UL, CSA and ARI certification not available.

Provided by: Construction - Nicholas Beaudin

1

Designed by: Construction - Oasis International

Specifications subject to change without notice

Published on: 3/1/2016 ver. 2011

Updated on: 3/1/2016 ver. 2011

## OASIS® BARRIER-FREE SPLIT-LEVEL Versacooler® II MODELS PACSL, P8ACSL, PGACSL, PG8ACSL, P8ACSLEE

